D-RINGS > MOUNTING D RINGS

2-5/16" Bolt-On / Weldable D-Ring with Mounting Bracket - Unfinished - 12,000 lbs. BS

SKU: MR8UF Item weight: 1.08 lbs

WORKING LOAD LIMIT	BREAK STRENGTH	WIDTH
4,000 lbs.	12,000 lbs.	2.7"

SPECIFICATIONS

SKU	MR8UF
Working Load Limit (lbs.)	4,000 lbs.
Assembly Break Strength	12,000 lbs.
Size	2-5/16"
Diameter	2-5/16"
Inside Width	2.7"
Type	Bolt On
Product Weight	.8 lbs.
Quantity	Single
Additional Info	This item is not rated for overhead lifting - for tie down use only.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/mounting-ring-2-5-16-x-12-000-lbs_2

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 12, 2026.