WIRE ROPE SLINGS > TYPE 215 MECHANICAL SPLICE GROMMETS

# 5/16" x 3' Mechanical Splice Grommet Wire Rope Sling

SKU: MSG-516-3 Item weight: 1.2 lbs

| LENGTH | CAPACITY |
|---|---|
| 3' | 1.6 ton |

## SPECIFICATIONS

| | |
|---|---|
| **SKU** | MSG-516-3 |
| **Safety Factor** | 5:1 |
| **30 Degree Capacity** | 1.6 ton |
| **45 Degree Capacity** | 1.5 ton |
| **60 Degree Capacity** | 1.8 ton |
| **Vertical Capacity** | 1.6 ton |
| **Choker Capacity** | 1.2 ton |
| **Basket Capacity** | 3.3 ton |
| **Diameter** | 5/16" |
| **Length** | 3' |
| **Body Diameter** | 5/16" |
| **Wire Rope Class** | 6x36WS |
| **Standards** | Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements. |

## SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.

**Current price & availability: heavyhaulrigging.com/p/5-16-x-3-mechanical-splice-grommet-wire-rope-sling**


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.