D-RINGS > PAN FITTINGS

Bolt-On Flush-Mount D-Ring - Galvanized - 1,200 lbs. BS

SKU: PF5ZC Item weight: 0.3 lbs

WORKING LOAD LIMIT	BREAK STRENGTH	WIDTH
400 lbs.	1,200 lbs.	1.15"

SPECIFICATIONS

SKU	PF5ZC
Working Load Limit (lbs.)	400 lbs.
Assembly Break Strength	1,200 lbs.
Inside Width	1.15"
Finish	Zinc
Type	Bolt On
Product Weight	.3 lbs.
Quantity	Single
Additional Info	This item is not rated for overhead lifting - for tie down use only. Hardware NOT included

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/mounting-ring-flush-mount-zinc-plated-1-200-lb

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 20, 2026.