POLYESTER ROUND SLINGS > ENDLESS POLYESTER SLING

# 4' Domestic Endless Round Sling - Polyester | 10,600 lbs. Capacity

SKU: PRS4-4 Item weight: 3.1 lbs

**LENGTH**
**4'**

**CAPACITY**
**10,600 lbs. basket capacity**

## SPECIFICATIONS

| | |
|---|---|
| **SKU** | PRS4-4 |
| **Safety Factor** | 5:1 |
| **Rated for Overhead Lifting** | Yes |
| **30 Degree Capacity** | 10,600 lbs. basket capacity |
| **45 Degree Capacity** | 15,000 lbs. basket capacity |
| **60 Degree Capacity** | 18,400 lbs. basket capacity |
| **Vertical Capacity** | 10,600 lbs. |
| **Choker Capacity** | 8,500 lbs. |
| **Basket Capacity** | 21,200 lbs. |
| **Length** | 4' |
| **Body Diameter** | 1.2" |
| **Color** | Tan |
| **Product Weight** | 2.4 lbs. |
| **Standards** | Meets or exceeds all ASME B30.26 requirements. |
| **Additional Info** | All Nylon and Polyester lifting slings have a length tolerance of +/- 2%. |


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.

## SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

**Current price & availability: heavyhaulrigging.com/p/endless-polyester-round-lifting-sling-4-tan**



Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.