POLYESTER ROUND SLINGS > EYE & EYE POLYESTER SLING

# 9' Domestic Eye & Eye Round Sling - Polyester | 25,000 lbs. Capacity

SKU: PRS8EE-9 Item weight: 11.7 lbs

**LENGTH**
**20"**

**CAPACITY**
**25,000 lbs. basket capacity**

## SPECIFICATIONS

| | |
|---|---|
| **SKU** | PRS8EE-9 |
| **Safety Factor** | 5:1 |
| **Rated for Overhead Lifting** | Yes |
| **30 Degree Capacity** | 25,000 lbs. basket capacity |
| **45 Degree Capacity** | 35,400 lbs. basket capacity |
| **60 Degree Capacity** | 43,300 lbs. basket capacity |
| **Vertical Capacity** | 25,000 lbs. |
| **Choker Capacity** | 20,000 lbs. |
| **Basket Capacity** | 50,000 lbs. |
| **Eye Length** | 20" |
| **Length** | 9' |
| **Body Diameter** | 2" |
| **Color** | Orange |
| **Product Weight** | 11.7 lbs. |
| **Standards** | Meets or exceeds all ASME B30.26 requirements. |
| **Additional Info** | All Nylon and Polyester lifting slings have a length tolerance of +/- 2%. |


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 12, 2026.

### SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

**Current price & availability: heavyhaulrigging.com/p/polyester-round-eye-eye-lifting-sling-9-orange_2**



Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 12, 2026.