LOAD CELLS > TENSION LOAD CELLS

Straightpoint® 35 T Radiolink Plus - RLP35T

SKU: RLP-35-T Item weight: 19 lbs

CAPACITY

77,000 lbs.

SPECIFICATIONS

SKU	RLP-35-T
Safety Factor	5:1
Load Capacity	77,000 lbs.
Pin Size	2-1/4"
Type	Standard Load Cell
Power Source	Handheld: 2 x AA batteries | Loadcell: 4 x AA batteries
Accuracy	+/- 0.1% of Full Scale
Resolution	10 lbs.
Range	3,280'
Data Rate	3Hz - up to 200Hz can be ordered for dynamic load monitorning applications
Operating Temperature	-10° to +50°C | 14° to 122° F
Battery Life	Handheld: 40 hours continuous | Loadcell: 1,200 hours continuous
Display Type	240x128 Multi-Line Dot Matrix with Backlight
Product Weight	19 lbs.
Standards	IP67
Manufacturer Name	Crosby Straightpoint
Brand Part Number	RLP35T / 2789091

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 20, 2026.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/straightpoint-35-t-radiolink-plus-rlp35t

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 20, 2026.