LIFTING BEAMS AND SPREADER BARS > SPREADER BEAM ADJUSTABLE 20-50 TONS

50 Tons x 14 - 20' Adjustable Spreader Beam

SKU: SBA100K240 Item weight: 1,265 lbs

WORKING LOAD LIMIT
100,000 lbs.

MATERIAL
Steel

SPECIFICATIONS

SKU	SBA100K240
Working Load Limit (lbs.)	100,000 lbs.
Safety Factor	3:1
Rated for Overhead Lifting	Yes
Spread	14' - 20'
Material	Steel
Finish	High visibility yellow powder coated paint
Product Weight	1,250 lbs.
Standards	Exceeds all ASME B30.20 and OSHA regulations. Proof loaded per OSHA requirements.
Manufacturer Name	M&W
Brand Part Number	20139
Additional Info	WLL (tons): 50 Headroom: 9.3" Spread Adjustment Increments: 6" Minimum horizontal top rigging angle of 45°; M&W recommends a min of 60°

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 12, 2026.

Current price & availability: heavyhaulrigging.com/p/spreader-beam-adjustable-100-000-lb-capacity-14-20-spread

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 12, 2026.