LIFTING BEAMS AND SPREADER BARS > SPREADER BEAM ADJUSTABLE 2-10 TONS

10 Tons x 12 - 20' Adjustable Spreader Beam

SKU: SBA20K240 Item weight: 520 lbs

WORKING LOAD LIMIT
20,000 lbs.

MATERIAL
Steel

SPECIFICATIONS

SKU	SBA20K240
Working Load Limit (lbs.)	20,000 lbs.
Safety Factor	3:1
Rated for Overhead Lifting	Yes
Throat Opening	1.31"
Spread	12' - 20'
End Fitting	Bottom Swivel Latch Hooks Included
Material	Steel
Finish	High visibility yellow powder coated paint
Product Weight	505 lbs.
Standards	Exceeds all ASME B30.20 and OSHA regulations. Proof loaded per OSHA requirements.
Manufacturer Name	M&W
Brand Part Number	12885
Additional Info	WLL (tons): 10 Headroom: 7.63" Spread Adjustment Increments: 1" Minimum horizontal top rigging angle of 45°; M&W recommends a min of 60°

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/spreader-beam-adjustable-20-000-lb-capacity-12-to-20-spread

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.