



LIFTING BEAMS AND SPREADER BARS > SPREADER BEAM ADJUSTABLE 20-50 TONS

30 Tons x 14 - 20' Adjustable Spreader Beam

SKU: SBA60K240 Item weight: 905 lbs

WORKING LOAD LIMIT	MATERIAL
60,000 lbs.	Steel

SPECIFICATIONS

SKU	SBA60K240
Working Load Limit (lbs.)	60,000 lbs.
Safety Factor	3:1
Rated for Overhead Lifting	Yes
Spread	14' - 20'
Material	Steel
Finish	High visibility yellow powder coated paint
Product Weight	890 lbs.
Standards	Exceeds all ASME B30.20 and OSHA regulations. Proof loaded per OSHA requirements.
Manufacturer Name	M&W
Brand Part Number	20129
Additional Info	WLL (tons): 30 Headroom: 7.1" Spread Adjustment Increments: 6" Minimum horizontal top rigging angle of 45°; M&W recommends a min of 60°

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.



Current price & availability: heavyhaulrigging.com/p/spreader-beam-adjustable-60-000-lb-capacity-14-20-spread