LIFTING BEAMS AND SPREADER BARS > SPREADER BEAM FIXED 20-50 TONS

50 Tons x 12' Spreader Beam | Fixed Length

SKU: SBF100K144 Item weight: 730 lbs

WORKING LOAD LIMIT
100,000 lbs.

MATERIAL
Steel

SPECIFICATIONS

SKU	SBF100K144
Working Load Limit (lbs.)	100,000 lbs.
Safety Factor	3:1
Rated for Overhead Lifting	Yes
Spread	12'
Material	Steel
Finish	High visibility yellow powder coated paint
Product Weight	715 lbs.
Standards	Exceeds all ASME B30.20 and OSHA regulations. Proof loaded per OSHA requirements.
Manufacturer Name	M&W
Brand Part Number	20190
Additional Info	WLL (tons): 50 Headroom: 9.8" Minimum horizontal top rigging angle of 45°; M&W recommends a min of 60°

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 12, 2026.

Current price & availability: heavyhaulrigging.com/p/spreader-beam-fixed-length-100-000-lb-capacity-12-max-spread

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 12, 2026.