

LIFTING BEAMS AND SPREADER BARS > SPREADER BEAM FIXED 2-10 TONS

5 Tons x 8' Spreader Beam | Fixed Length

SKU: SBF10K96 Item weight: 127 lbs

WORKING LOAD LIMIT	MATERIAL
10,000 lbs.	Steel

SPECIFICATIONS

SKU	SBF10K96
Working Load Limit (lbs.)	10,000 lbs.
Safety Factor	3:1
Rated for Overhead Lifting	Yes
Throat Opening	1.08"
Spread	8'
End Fitting	Bottom Swivel Latch Hooks Included
Material	Steel
Finish	High visibility yellow powder coated paint
Product Weight	112 lbs.
Standards	Exceeds all ASME B30.20 and OSHA regulations. Proof loaded per OSHA requirements.
Manufacturer Name	M&W
Brand Part Number	13122

Additional Info	WLL (tons): 5 Headroom: 8.98" Minimum horizontal top rigging angle of 45°; M&W recommends a min of 60°
-----------------	--

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/spreader-beam-fixed-length-10-000-lb-capacity-8-max-spread