

LIFTING BEAMS AND SPREADER BARS > SPREADER BEAM FIXED 20-50 TONS

40 Tons x 4' Spreader Beam | Fixed Length

SKU: SBF80K48 Item weight: 405 lbs

WORKING LOAD LIMIT	MATERIAL
80,000 lbs.	Steel

SPECIFICATIONS

SKU	SBF80K48
Working Load Limit (lbs.)	80,000 lbs.
Safety Factor	3:1
Rated for Overhead Lifting	Yes
Spread	4'
Material	Steel
Finish	High visibility yellow powder coated paint
Product Weight	390 lbs.
Standards	Exceeds all ASME B30.20 and OSHA regulations. Proof loaded per OSHA requirements.
Manufacturer Name	M&W
Brand Part Number	20179
Additional Info	WLL (tons): 40 Headroom: 9.8" Minimum horizontal top rigging angle of 45°; M&W recommends a min of 60°

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/spreader-beam-fixed-length-80-000-lb-capacity-4-max-spread