WIRE ROPE > 1X19 EHS GUY STRAND WIRE ROPE

3/4" 1x19 EHS Galvanized Guy Wire | 2,500 ft.

SKU: SC119EHSGS34-2500FT Item weight: 2,875 lbs

BREAK STRENGTH	GRADE	LENGTH
29.15 tons / 58,300 lbs.	EHS	2,500'

SPECIFICATIONS

SKU	SC119EHSGS34-2500FT
Assembly Break Strength	29.15 tons / 58,300 lbs.
Grade	EHS
Wire Rope Diameter	3/4"
Length	2,500'
Wire Rope Class	1x19
Finish	Galvanized
Product Weight	2,875 lbs.
Weight Per Foot	1.15 lbs.
Standards	Meets all requirements of ASTM A475-03
Additional Info	Category 2 Rotation-Resistant Rope Right Hand Regular Lay

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/3-4-1x19-ehs-galvanized-guy-wire-2-500-ft

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 13, 2026.