WIRE ROPE > 19X19 COMPACTED BRIGHT WIRE ROPE

1/2" 19x19 Compacted Rotation-Resistant Wire Rope - EIPS IWRC | 2,500 ft.

SKU: SC12CBW1919-2500FT Item weight: 1,350 lbs

BREAK STRENGTH	GRADE	LENGTH
14.88 tons / 29,760 lbs.	EIPS	2,500'

SPECIFICATIONS

SKU	SC12CBW1919-2500FT
Assembly Break Strength	14.88 tons / 29,760 lbs.
Rated for Overhead Lifting	Yes
Grade	EIPS
Wire Rope Diameter	1/2"
Length	2,500'
Wire Rope Class	19x19
Core	IWRC
Finish	Bright
Product Weight	1,350 lbs.
Weight Per Foot	0.54 lbs.
Standards	Meets all dimensional and strength requirements of Federal Specification RR-W-410 (latest revision) and ASTM A1023
Additional Info	Category 2 Rotation-Resistant Rope Right Hand Regular Lay

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 13, 2026.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/1-2-19x19-compacted-rotation-resistant-wire-rope-eips-iwrc-2-500-ft

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 13, 2026.