WIRE ROPE > 1X7 EHS GUY STRAND WIRE ROPE

# 1/2" 1x7 EHS Galvanized Guy Wire | 2,500 ft.

SKU: SC17EHSGS12-2500FT Item weight: 1,300 lbs

| BREAK STRENGTH | GRADE | LENGTH |
|---|---|---|
| 13.45 tons / 26,900 lbs. | EHS | 2,500' |

## SPECIFICATIONS

| | |
|---|---|
| **SKU** | SC17EHSGS12-2500FT |
| **Assembly Break Strength** | 13.45 tons / 26,900 lbs. |
| **Grade** | EHS |
| **Wire Rope Diameter** | 1/2" |
| **Length** | 2,500' |
| **Wire Rope Class** | 1x7 |
| **Core** | IWRC |
| **Finish** | Galvanized |
| **Product Weight** | 1,300 lbs. |
| **Weight Per Foot** | 0.52 lbs. |
| **Standards** | Meets all requirements of ASTM A475-03 |

### SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

**Current price & availability: heavyhaulrigging.com/p/1-2-1x7-ehs-galvanized-guy-wire-2-500-ft**


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 1, 2026.