

WIRE ROPE > 6X19 STAINLESS STEEL WIRE ROPE

7/16" 6x19 Stainless Steel Wire Rope - Type 304 IWRC | 2,500' Coil

SKU: SC716SI304619 Item weight: 890 lbs

BREAK STRENGTH	GRADE	LENGTH
8.15 tons / 16,300 lbs.	304 Stainless Steel	2,500'

SPECIFICATIONS

SKU	SC716SI304619
Assembly Break Strength	8.15 tons / 16,300 lbs.
Rated for Overhead Lifting	Yes
Grade	304 Stainless Steel
Wire Rope Diameter	7/16"
Length	2,500'
Wire Rope Class	6x19
Core	IWRC
Product Weight	890 lbs.
Weight Per Foot	0.356
Standards	Meets all dimensional and strength requirements of Federal Specification RR-W-410 (latest revision) and ASTM A1023
Additional Info	Right Hand Regular Lay

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/stainless-steel-wire-rope-304-6x19-class-7-16-2500-coil