

RIGGING HOOKS > EYE HOIST HOOK

Swivel Eye Hoist Hook - 3 Ton

SKU: SEHHOOK3T Item weight: 3 lbs

|                    |                |
|--------------------|----------------|
| WORKING LOAD LIMIT | BREAK STRENGTH |
| 6,000 lbs.         | 30,000 lbs.    |

SPECIFICATIONS

|                           |                                                                |
|---------------------------|----------------------------------------------------------------|
| SKU                       | SEHHOOK3T                                                      |
| Working Load Limit (lbs.) | 6,000 lbs.                                                     |
| Assembly Break Strength   | 30,000 lbs.                                                    |
| Safety Factor             | 5:1                                                            |
| Eye Diameter              | 0.71"                                                          |
| Jaw Opening               | 1.26"                                                          |
| Product Weight            | 3 lbs.                                                         |
| Standards                 | Meets or exceeds ASTM A952 / A952M & ASME B30.10 requirements. |
| Additional Info           | Eye Dimensions: 1.97"W x 1.85"L Thread Size: M20 WLL (tons): 3 |

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: [heavyhaulrigging.com/p/swivel-eye-hoist-hook-3-ton](https://heavyhaulrigging.com/p/swivel-eye-hoist-hook-3-ton)