RIGGING HOOKS > SWIVEL EYE HOOK

Swivel Eye Hook - Stainless Steel 5"

SKU: SEHSS5 Item weight: 0.7 lbs

WORKING LOAD LIMIT	BREAK STRENGTH	GRADE	CHAIN SIZE
1,430 lbs.	5,720 lbs.	316 Stainless...	5/16"

SPECIFICATIONS

SKU	SEHSS5
Working Load Limit (lbs.)	1,430 lbs.
Assembly Break Strength	5,720 lbs.
Safety Factor	4:1
Grade	316 Stainless Steel
Chain Size	5/16"
Product Weight	.7 lbs.
Brand Part Number	4322S-08

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/swivel-eye-hook-stainless-steel-5

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 11, 2026.