RIGGING HOOKS > SWIVEL EYE HOOK

Swivel Eye Hook - Stainless Steel 6"

SKU: SEHSS6 Item weight: 1.18 lbs

WORKING LOAD LIMIT	BREAK STRENGTH	GRADE	CHAIN SIZE
2,250 lbs.	9,000 lbs.	316 Stainless...	3/8"

SPECIFICATIONS

SKU	SEHSS6
Working Load Limit (lbs.)	2,250 lbs.
Assembly Break Strength	9,000 lbs.
Safety Factor	4:1
Grade	316 Stainless Steel
Chain Size	3/8"
Product Weight	1.18 lbs.
Brand Part Number	4322S-10

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/swivel-eye-hook-stainless-steel-6

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 11, 2026.