MOVING SUPPLIES > PACKAGING SUPPLIES

1-1/4" Composite Strapping Starter Kit - Forklift Dispenser

SKU: SKFD-CC105UF-CS Item weight: 87.92 lbs

BREAK STRENGTH	GRADE	LENGTH	MATERIAL
4960 lbf	AAR Grade 4 &...	951' per roll	High tenacity p...

SPECIFICATIONS

SKU	SKFD-CC105UF-CS
Assembly Break Strength	4960 lbf
Grade	AAR Grade 4 & DNV Witnessed
Size	1-1/4"
Length	951' per roll
Core	8" Diameter
Material	High tenacity polyester filament yarn and homopolymer polypropylene
Color	White
Operating Temperature	Use between 23°F and 104°F. Store in cool and dry environment.
Product Weight	84.42 lbs.
Brand	Cordstrap
Additional Info	System Breaking Strength: 4960 lbf Linear Breaking Strength: 3580 lbf Elongation at break: 12%

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/1-1-4-composite-strapping-starter-kit-forklift-dispenser

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.