MOVING SUPPLIES > PACKAGING SUPPLIES

5/8" Composite Strapping Starter Kit - Mobile Dispenser

SKU: SKMD-CC55UF-CS Item weight: 111.45 lbs

BREAK STRENGTH	GRADE	LENGTH	MATERIAL
1940 lbf	DNV Witnessed	2296' per roll	High tenacity p...

SPECIFICATIONS

SKU	SKMD-CC55UF-CS
Assembly Break Strength	1940 lbf
Grade	DNV Witnessed
Size	5/8"
Length	2296' per roll
Core	8" Diameter
Material	High tenacity polyester filament yarn and homopolymer polypropylene
Color	White
Operating Temperature	Use between 23°F and 104°F. Store in cool and dry environment.
Product Weight	110.99 lbs.
Brand	Cordstrap
Additional Info	System Breaking Strength: 1940 lbf Linear Breaking Strength: 1212 lbf Elongation at break: 12%

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.

Current price & availability: heavyhaulrigging.com/p/5-8-composite-strapping-starter-kit-mobile-dispenser

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.