MOVING SUPPLIES > PACKAGING SUPPLIES

1" Composite Strapping Starter Kit - Mobile Dispenser

SKU: SKMD-CC86UF-CS Item weight: 122.65 lbs

BREAK STRENGTH	GRADE	LENGTH	MATERIAL
3306 lbf	DNV Witnessed	1443' per roll	High tenacity p...

SPECIFICATIONS

SKU	SKMD-CC86UF-CS
Assembly Break Strength	3306 lbf
Grade	DNV Witnessed
Size	1"
Length	1443' per roll
Core	8" Diameter
Material	High tenacity polyester filament yarn and homopolymer polypropylene
Color	White
Operating Temperature	Use between 23°F and 104°F. Store in cool and dry environment.
Product Weight	116.76 lbs.
Brand	Cordstrap
Additional Info	System Breaking Strength: 3306 lbf Linear Breaking Strength: 2039 lbf Elongation at break: 12%

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 14, 2026.

Current price & availability: heavyhaulrigging.com/p/1-composite-strapping-starter-kit-mobile-dispenser

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 14, 2026.