EYE BOLTS > CROSBY SL-150 HOIST RING

Crosby® 5/8" Slide-Loc™ - SL-150

SKU: SLDLC58-CR Item weight: 1.33 lbs

WORKING LOAD LIMIT	LENGTH	MATERIAL
3,000 lbs.	1-5/8" Bolt	Alloy Steel

SPECIFICATIONS

SKU	SLDLC58-CR
Working Load Limit (lbs.)	3,000 lbs.
Safety Factor	4:1
Rated for Overhead Lifting	Yes
Diameter	5/8" - 11 Bolt
Length	1-5/8" Bolt
Thread Type	UNC
Material	Alloy Steel
Finish	Zinc Plated
Torque	No torque wrench required.
Product Weight	1.1 lbs.
Standards	Meets or exceeds ASME B30.26 requirements.
Manufacturer Name	Crosby®
Brand Part Number	1068425
Additional Info	Effective Thread Projection: 1 in

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/crosby-5-8-slide-loc-sl-150

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.