EYE BOLTS > CROSBY SL-150 HOIST RING

Crosby® 7/8" Slide-Loc™ - SL-150

SKU: SLDLC78-CR Item weight: 2.63 lbs

WORKING LOAD LIMIT	LENGTH	MATERIAL
4,600 lbs.	2" Bolt	Alloy Steel

SPECIFICATIONS

SKU	SLDLC78-CR
Working Load Limit (lbs.)	4,600 lbs.
Safety Factor	4:1
Rated for Overhead Lifting	Yes
Diameter	7/8" - 9 Bolt
Length	2" Bolt
Thread Type	UNC
Material	Alloy Steel
Finish	Zinc Plated
Torque	No torque wrench required.
Product Weight	2.16 lbs.
Standards	Meets or exceeds ASME B30.26 requirements.
Manufacturer Name	Crosby®
Brand Part Number	1068443
Additional Info	Effective Thread Projection: 1-2/9 in

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/crosby-7-8-slide-loc-sl-150

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.