BOLTHOLD ASPHALT ANCHORS

Bolthold SP10-38 Asphalt Anchor, Zinc Plated, 6 Pkg

SKU: SP10-38 Item weight: 2.5 lbs

LENGTH

6"

SPECIFICATIONS

SKU	SP10-38
Diameter	5/8"
Length	6"
Head Diameter	1.35"
Thread Type	3/8"-16 UNC Coarse Female Thread
Torque	200 lb.-in.
Manufacturer Name	Bolthold Asphalt anchors
Quantity	6
Additional Info	Shear Resistance: 1000 lbs. Pull Force: 1500 lbs.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/bolthold-sp10-38-asphalt-anchor-zinc-plated-6-pkg

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 14, 2026.