HIGH PERFORMANCE SLINGS > SINGLE-PATH ENDLESS ROUNDSLINGS

6" x 20' Single-Path High Performance Roundsling | Vertical Cap: 200,000 lbs.

SKU: SP20000CF-20 Item weight: 85 lbs

LENGTH	CAPACITY
20'	282,800 lbs.

SPECIFICATIONS

SKU	SP20000CF-20
Safety Factor	5.1
45 Degree Capacity	282,800 lbs.
60 Degree Capacity	346,400 lbs.
Vertical Capacity	200,000 lbs.
Choker Capacity	160,000 lbs.
Basket Capacity	400,000 lbs.
Length	20'
Minimum Connection Diameter	3"
Product Weight	85 lbs.
Additional Info	Nominal Body Width: 6" Minimum bending radius: 1.5"

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/6-x-20-single-path-high-performance-roundsling-vertical-cap-200-00...

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 16, 2026.