HIGH PERFORMANCE SLINGS > SINGLE-PATH ENDLESS ROUNDSLINGS

3" x 20' Single-Path High Performance Roundsling | Vertical Cap: 25,000 lbs.

SKU: SP2500CF-20 Item weight: 10.62 lbs

LENGTH	CAPACITY
20'	35,350 lbs.

SPECIFICATIONS

SKU	SP2500CF-20
Safety Factor	5.1
45 Degree Capacity	35,350 lbs.
60 Degree Capacity	43,300 lbs.
Vertical Capacity	25,000 lbs.
Choker Capacity	20,000 lbs.
Basket Capacity	50,000 lbs.
Length	20'
Minimum Connection Diameter	1"
Product Weight	10.62 lbs.
Additional Info	Nominal Body Width: 3" Minimum bending radius: .5"

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/3-x-20-single-path-high-performance-roundsling-vertical-cap-25-000-...

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.