

HIGH PERFORMANCE SLINGS > SINGLE-PATH ENDLESS ROUNDSLINGS

5" x 16' Single-Path High Performance Roundsling | Vertical Cap: 85,000 lbs.

SKU: SP8500CF-16 Item weight: 22.82 lbs

LENGTH	CAPACITY
16'	120,190 lbs.

SPECIFICATIONS

SKU	SP8500CF-16
Safety Factor	5.1
45 Degree Capacity	120,190 lbs.
60 Degree Capacity	147,220 lbs.
Vertical Capacity	85,000 lbs.
Choker Capacity	68,000 lbs.
Basket Capacity	170,000 lbs.
Length	16'
Minimum Connection Diameter	1.84"
Product Weight	22.81 lbs.
Additional Info	Nominal Body Width: 5" Minimum bending radius: .92"

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/5-x-16-single-path-high-performance-roundsling-vertical-cap-85-000-...