WIRE ROPE SLINGS > TYPE 110 SPELTER SOCKET

1-1/4" x 8' Closed and Closed Spelter Socket Wire Rope Sling

SKU: SPS-CSCS-1-14-8 Item weight: 80 lbs

WORKING LOAD LIMIT	BREAK STRENGTH	LENGTH
31,960 lbs.	79.9 ton	8'

SPECIFICATIONS

SKU	SPS-CSCS-1-14-8
Working Load Limit (lbs.)	31,960 lbs.
Assembly Break Strength	79.9 ton
Safety Factor	5:1
Diameter	1-1/4"
Length	8'
Wire Rope Class	6x36WS
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.
Additional Info	WLL (tons): 15.98

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/1-1-4-x-8-closed-and-closed-spelter-socket-wire-rope-sling

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.