WIRE ROPE SLINGS > TYPE 110 SPELTER SOCKET

# 3/8" x 8' Open and Closed Spelter Socket Wire Rope Sling

SKU: SPS-OSCS-38-8 Item weight: 10 lbs

| WORKING LOAD LIMIT | BREAK STRENGTH | LENGTH |
|---|---|---|
| 3,020 lbs. | 7.55 ton | 8' |

## SPECIFICATIONS

| | |
|---|---|
| **SKU** | SPS-OSCS-38-8 |
| **Working Load Limit (lbs.)** | 3,020 lbs. |
| **Assembly Break Strength** | 7.55 ton |
| **Safety Factor** | 5:1 |
| **Diameter** | 3/8" |
| **Length** | 8' |
| **Wire Rope Class** | 6x36WS |
| **Standards** | Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements. |
| **Additional Info** | WLL (tons): 1.51 |

### SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

**Current price & availability: heavyhaulrigging.com/p/3-8-x-8-open-and-closed-spelter-socket-wire-rope-sling**


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 21, 2026.