WIRE ROPE SLINGS > TYPE 110 SPELTER SOCKET

5/8" x 18' Open and Closed Spelter Socket Wire Rope Sling

SKU: SPS-OSCS-58-18 Item weight: 20 lbs

WORKING LOAD LIMIT	BREAK STRENGTH	LENGTH
8,240 lbs.	20.6 ton	18'

SPECIFICATIONS

SKU	SPS-OSCS-58-18
Working Load Limit (lbs.)	8,240 lbs.
Assembly Break Strength	20.6 ton
Safety Factor	5:1
Diameter	5/8"
Length	18'
Wire Rope Class	6x36WS
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.
Additional Info	WLL (tons): 4.12

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/5-8-x-18-open-and-closed-spelter-socket-wire-rope-sling

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 21, 2026.