WIRE ROPE SLINGS > TYPE 110 SPELTER SOCKET

1-1/2" x 20' Open and Open Spelter Socket Wire Rope Sling

SKU: SPS-OSOS-1-12-20 Item weight: 120 lbs

WORKING LOAD LIMIT	BREAK STRENGTH	LENGTH
45,600 lbs.	114 ton	20'

SPECIFICATIONS

SKU	SPS-OSOS-1-12-20
Working Load Limit (lbs.)	45,600 lbs.
Assembly Break Strength	114 ton
Safety Factor	5:1
Diameter	1-1/2"
Length	20'
Wire Rope Class	6x36WS
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.
Additional Info	WLL (tons): 22.8

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/1-1-2-x-20-open-and-open-spelter-socket-wire-rope-sling

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 21, 2026.