WIRE ROPE SLINGS > SINGLE LEG 6X19

# 7/8" x 8' Standard Eye Wire Rope Sling

SKU: SW1-78-8 Item weight: 20.37 lbs

| GRADE | LENGTH | CAPACITY | MATERIAL |
|---|---|---|---|
| EIPS | 8' | 7.6 tons / 15,20... | Bright Steel Wi... |

## SPECIFICATIONS

| | |
|---|---|
| **SKU** | SW1-78-8 |
| **Safety Factor** | 5:1 |
| **30 Degree Capacity** | 7.6 tons / 15,200 lbs. Angled Basket Hitch |
| **45 Degree Capacity** | 11 tons / 22,000 lbs. Angled Basket Hitch |
| **60 Degree Capacity** | 13 tons / 26,000 lbs. Angled Basket Hitch |
| **Vertical Capacity** | 7.6 tons / 15,200 lbs. |
| **Choker Capacity** | 5.6 tons / 11,200 lbs. |
| **Basket Capacity** | 15 tons / 30,000 lbs. |
| **Grade** | EIPS |
| **Diameter** | 7/8" |
| **Length** | 8' |
| **Core** | IWRC |
| **End Fitting** | Flemish Eye |
| **Material** | Bright Steel Wire Rope |
| **Product Weight** | 20.37 lbs. |
| **Standards** | Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements. |
| **Additional Info** | Eye dimensions: 7"W x 14"L Rated capacities for basket hitch based on a D/d ratio of 25 |


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 21, 2026.

## SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

**Current price & availability: heavyhaulrigging.com/p/wire-rope-sling-single-leg-6x19-7-8-x-8**



Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 21, 2026.