

WIRE ROPE SLINGS > EYE AND THIMBLE WIRE ROPE SLING

3/4" x 8' Standard Eye & Thimble Wire Rope Sling

SKU: SW1-E-TH-34-8 Item weight: 14.7 lbs

GRADE	LENGTH	CAPACITY	MATERIAL
EIPS	8'	5.6 tons / 11,20...	Bright Steel Wi...

SPECIFICATIONS

SKU	SW1-E-TH-34-8
Safety Factor	5:1
30 Degree Capacity	5.6 tons / 11,200 lbs. Angled Basket Hitch
45 Degree Capacity	7.9 tons / 15,800 lbs. Angled Basket Hitch
60 Degree Capacity	9.7 tons / 19,400 lbs. Angled Basket Hitch
Vertical Capacity	5.6 tons / 11,200 lbs.
Choker Capacity	4.1 tons / 8,200 lbs.
Basket Capacity	11 tons / 22,000 lbs.
Grade	EIPS
Diameter	3/4"
Length	8'
Core	IWRC
End Fitting	Thimble Eye & Standard Eye
Material	Bright Steel Wire Rope
Product Weight	14.7 lbs.
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.
Additional Info	Eye dimensions: 6"W x 12"L Thimble dimensions: 2"W x 3-3/4"L Rated capacities for basket hitch based on a D/d ratio of 25

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/wire-rope-sling-single-leg-6x19-eye-and-thimble-3-4-x-8