

WIRE ROPE SLINGS > EYE AND THIMBLE WIRE ROPE SLING

5/8" x 8' Standard Eye & Thimble Wire Rope Sling

SKU: SW1-E-TH-58-8 Item weight: 9.39 lbs

GRADE	LENGTH	CAPACITY	MATERIAL
EIPS	8'	3.9 tons / 7,800...	Bright Steel Wi...

SPECIFICATIONS

SKU	SW1-E-TH-58-8
Safety Factor	5:1
30 Degree Capacity	3.9 tons / 7,800 lbs. Angled Basket Hitch
45 Degree Capacity	5.5 tons / 11,000 lbs. Angled Basket Hitch
60 Degree Capacity	6.8 tons / 13,600 lbs. Angled Basket Hitch
Vertical Capacity	3.9 tons / 7,800 lbs.
Choker Capacity	2.9 tons / 5,800 lbs.
Basket Capacity	7.8 tons / 15,600 lbs.
Grade	EIPS
Diameter	5/8"
Length	8'
Core	IWRC
End Fitting	Thimble Eye & Standard Eye
Material	Bright Steel Wire Rope
Product Weight	9.39 lbs.
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.
Additional Info	Eye dimensions: 5"W x 10"L Thimble dimensions: 1-3/4"W x 3-1/4"L Rated capacities for basket hitch based on a D/d ratio of 25

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/wire-rope-sling-single-leg-6x19-eye-and-thimble-5-8-x-8