WIRE ROPE SLINGS > 2 LEG BRIDLE

1" x 16' 2-Leg Wire Rope Bridle Sling with Eye Hooks

SKU: SW2-1-16 Item weight: 150.56 lbs

GRADE	LENGTH	CAPACITY	MATERIAL
EIPS	16'	9.8 tons / 19,60...	Bright Steel Wi...

SPECIFICATIONS

SKU	SW2-1-16
Safety Factor	5:1
30 Degree Capacity	9.8 tons / 19,600 lbs.
45 Degree Capacity	14 tons / 28,000 lbs.
60 Degree Capacity	17 tons / 34,000 lbs.
Grade	EIPS
Diameter	1"
Length	16'
Core	IWRC
End Fitting	10 ton carbon steel hook
Material	Bright Steel Wire Rope
Product Weight	150.56 lbs.
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.
Additional Info	1-1/2" master link diameter Rated capacities for basket hitch based on a D/d ratio of 25

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/wire-rope-sling-2-leg-bridle-1-x-16

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.