WIRE ROPE SLINGS > 2 LEG BRIDLE

5/8" x 16' 2-Leg Wire Rope Bridle Sling with Eye Hooks

SKU: SW2-58-16 Item weight: 57.19 lbs

GRADE	LENGTH	CAPACITY	MATERIAL
EIPS	16'	3.9 tons / 7,800...	Bright Steel Wi...

SPECIFICATIONS

SKU	SW2-58-16
Safety Factor	5:1
30 Degree Capacity	3.9 tons / 7,800 lbs.
45 Degree Capacity	5.5 tons / 11,000 lbs.
60 Degree Capacity	6.8 tons / 13,600 lbs.
Grade	EIPS
Diameter	5/8"
Length	16'
Core	IWRC
End Fitting	5 ton carbon steel hook
Material	Bright Steel Wire Rope
Product Weight	57.19 lbs.
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.
Additional Info	1" master link diameter Rated capacities for basket hitch based on a D/d ratio of 25

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/5-8-x-16-2-leg-wire-rope-bridle-sling

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.