

WIRE ROPE SLINGS > 3 LEG BRIDLE

7/8" x 12' 3-Leg Wire Rope Bridle Sling with Eye Hooks

SKU: SW3-78-12 Item weight: 140.45 lbs

GRADE	LENGTH	CAPACITY	MATERIAL
EIPS	12'	11 tons / 22,00...	Bright Steel Wi...

SPECIFICATIONS

SKU	SW3-78-12
Safety Factor	5:1
30 Degree Capacity	11 tons / 22,000 lbs.
45 Degree Capacity	16 tons / 32,000 lbs.
60 Degree Capacity	20 tons / 40,000 lbs.
Grade	EIPS
Diameter	7/8"
Length	12'
Core	IWRC
End Fitting	7.5 ton carbon steel hook
Material	Bright Steel Wire Rope
Product Weight	140.45 lbs.
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.
Additional Info	1-1/4" master link diameter Rated capacities for basket hitch based on a D/d ratio of 25

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/wire-rope-sling-3-leg-bridle-7-8-x-12