WIRE ROPE SLINGS > 4 LEG BRIDLE

# 1" x 16' 4-Leg Wire Rope Bridle Sling with Eye Hooks

SKU: SW4-1-16 Item weight: 305.67 lbs

| GRADE | LENGTH | CAPACITY | MATERIAL |
|---|---|---|---|
| EIPS | 16' | 20 tons / 40,00... | Bright Steel Wi... |

## SPECIFICATIONS

| | |
|---|---|
| **SKU** | SW4-1-16 |
| **Safety Factor** | 5:1 |
| **30 Degree Capacity** | 20 tons / 40,000 lbs. |
| **45 Degree Capacity** | 28 tons / 56,000 lbs. |
| **60 Degree Capacity** | 34 tons / 68,000 lbs. |
| **Grade** | EIPS |
| **Diameter** | 1" |
| **Length** | 16' |
| **Core** | IWRC |
| **End Fitting** | 10 ton carbon steel hook |
| **Material** | Bright Steel Wire Rope |
| **Product Weight** | 305.67 lbs. |
| **Standards** | Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements. |
| **Additional Info** | 1-7/8" master link diameter Rated capacities for basket hitch based on a D/d ratio of 25 |


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 18, 2026.

## SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

**Current price & availability: heavyhaulrigging.com/p/wire-rope-sling-4-leg-bridle-1-x-16**


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 18, 2026.