WIRE ROPE SLINGS > TYPE 115 SWAGE SOCKET

3/8" x 6' Closed and Closed Swage Socket Wire Rope Sling

SKU: SWS-CSCS-38-6 Item weight: 10 lbs

WORKING LOAD LIMIT	BREAK STRENGTH	LENGTH
3,020 lbs.	7.55 ton	6'

SPECIFICATIONS

SKU	SWS-CSCS-38-6
Working Load Limit (lbs.)	3,020 lbs.
Assembly Break Strength	7.55 ton
Safety Factor	5:1
Diameter	3/8"
Length	6'
Wire Rope Class	6x36WS
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.
Additional Info	WLL (tons): 1.51

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/3-8-x-6-closed-and-closed-swage-socket-wire-rope-sling

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.