



BULK CHAIN > GRADE 120 TIE DOWN CHAIN ASSEMBLIES

3/8" x 20' Tie Down Chain with Eye Grab Hooks | Grade 120

SKU: TC3820120-PWG Item weight: 39 lbs

WORKING LOAD LIMIT	BREAK STRENGTH	GRADE	CHAIN SIZE
10,600 lbs.	42,400 lbs.	120	3/8"

SPECIFICATIONS

SKU	TC3820120-PWG
Working Load Limit (lbs.)	10,600 lbs.
Assembly Break Strength	42,400 lbs.
Safety Factor	4:1
Rated for Overhead Lifting	No
Grade	120
Length	20'
Chain Size	3/8"
End Fitting	Grab Hook
Material	High Strength Alloy Steel
Finish	Powder Coated
Color	Blue
Operating Temperature	40°F / -40°C to 392°F / 200°C
Product Weight	39 lbs.
Standards	DOT-compliant; meets or exceeds FMCSA CFR49 Section 393.104 and NACM requirements. AWRF Accredited
Manufacturer Name	Pewag
Additional Info	Items are made to order and most ship same day - exceptions apply to large orders.

**SAFETY INFORMATION**

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- NOT FOR OVERHEAD LIFTING. This product is rated for cargo securement only.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/tie-down-chain-3-8-x-20-w-eye-grab-hooks-grade-120