BULK CHAIN > GRADE 100 BINDER CHAIN ASSEMBLIES

5/16" x 20' Tie Down Chain with Clevis Grab Hooks | Grade 100

SKU: TC51620100 Item weight: 23 lbs

WORKING LOAD LIMIT	BREAK STRENGTH	GRADE	CHAIN SIZE
5,700 lbs.	22,800 lbs.	100	5/16"

SPECIFICATIONS

SKU	TC51620100
Working Load Limit (lbs.)	5,700 lbs.
Assembly Break Strength	22,800 lbs.
Safety Factor	4:1
Rated for Overhead Lifting	No
Grade	100
Length	20'
Chain Size	5/16"
End Fitting	Clevis Grab Hook
Material	Alloy Steel
Finish	Powder Coated Chain
Product Weight	23 lbs.
Standards	DOT-compliant; meets or exceeds FMCSA CFR49 Section 393.104 and NACM requirements. AWRF Accredited
Manufacturer Name	KWB Chain / Import End Fittings
Additional Info	Made to order.

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- NOT FOR OVERHEAD LIFTING. This product is rated for cargo securement only.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/tie-down-chain-assembly-5-16-x-20-w-clevis-grab-hooks-grade-100

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.