

NYLON LIFTING SLINGS > TRIANGLE - TYPE 2

Nylon Lifting Sling - Triangle - 3" x 20' - 1-ply

SKU: TT1-903-20-T2 Item weight: 8.1 lbs

WIDTH	LENGTH	CAPACITY
3"	20'	4,700 lbs.

SPECIFICATIONS

SKU	TT1-903-20-T2
Safety Factor	5:1
Vertical Capacity	4,700 lbs.
Basket Capacity	9,400 lbs.
Width	3"
Length	20'
Plies	1
Product Weight	8.1 lbs.
Standards	Meets or exceeds all ASME B30.9 requirements.
Additional Info	All Nylon and Polyester lifting slings have a length tolerance of +/- 2%.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/nylon-lifting-sling-triangle-3-inch-wide-20-feet-long-1-ply