

HIGH PERFORMANCE SLINGS > TWIN-PATH ENDLESS ROUND SLINGS

3" x 8' Endless Twin-Path® High Performance Roundsling
| Vertical Cap: 10,000 lbs.

SKU: TUFXKS1000-8 Item weight: 2.4 lbs

LENGTH	CAPACITY
8'	14,140 lbs.

SPECIFICATIONS

SKU	TUFXKS1000-8
Safety Factor	5.1
45 Degree Capacity	14,140 lbs.
60 Degree Capacity	17,320 lbs.
Vertical Capacity	10,000 lbs.
Choker Capacity	8,000 lbs.
Basket Capacity	20,000 lbs.
Length	8'
Minimum Connection Diameter	0.63"
Product Weight	2.4 lbs.
Additional Info	Nominal Body Width: 3" Minimum bending radius: .32" Tapered Body Width: 1.5"

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/3-x-8-endless-twin-path-high-performance-roundsling-vertical-cap-10000-lbs