

HIGH PERFORMANCE SLINGS > TWIN-PATH ENDLESS ROUNDSLINGS

8" x 4' Endless Twin-Path® High Performance Roundsling
| Vertical Cap: 150,000 lbs.

SKU: TUFXKS15000-4 Item weight: 2.66 lbs

LENGTH	CAPACITY
4'	212,100 lbs.

SPECIFICATIONS

SKU	TUFXKS15000-4
Safety Factor	5.1
45 Degree Capacity	212,100 lbs.
60 Degree Capacity	259,800 lbs.
Vertical Capacity	150,000 lbs.
Choker Capacity	120,000 lbs.
Basket Capacity	300,000 lbs.
Length	4'
Minimum Connection Diameter	2.5"
Product Weight	2.66 lbs.
Additional Info	Nominal Body Width: 8" Minimum bending radius: 1.25" Tapered Body Width: 4"

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/8-x-4-endless-twin-path-high-performance-roundsling-vertical-cap-1...