

HIGH PERFORMANCE SLINGS > TWIN-PATH ENDLESS ROUNDSLINGS

4" x 16' Endless Twin-Path® High Performance Roundsling | Vertical Cap: 30,000 lbs.

SKU: TUFXKS3000-16 Item weight: 9.94 lbs

LENGTH	CAPACITY
16'	42,420 lbs.

SPECIFICATIONS

SKU	TUFXKS3000-16
Safety Factor	5.1
45 Degree Capacity	42,420 lbs.
60 Degree Capacity	51,960 lbs.
Vertical Capacity	30,000 lbs.
Choker Capacity	24,000 lbs.
Basket Capacity	60,000 lbs.
Length	16'
Minimum Connection Diameter	1.1"
Product Weight	9.94 lbs.
Additional Info	Nominal Body Width: 4" Minimum bending radius: .55" Tapered Body Width: 2"

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/4-x-16-endless-twin-path-high-performance-roundsling-vertical-cap-...