HIGH PERFORMANCE SLINGS > TWIN-PATH EYE & EYE ROUNDSLINGS

4" x 6' Eye & Eye Twin-Path® High Performance Roundsling | Vertical Cap: 30,000 lbs.

SKU: TUFXKS3000EE-6 Item weight: 2.25 lbs

LENGTH	CAPACITY
6'	30,000 lbs.

SPECIFICATIONS

SKU	TUFXKS3000EE-6
Safety Factor	5.1
Vertical Capacity	30,000 lbs.
Choker Capacity	24,000 lbs.
Basket Capacity	60,000 lbs.
Length	6'
Minimum Connection Diameter	1.1"
Product Weight	2.25 lbs.
Additional Info	Nominal Body Width: 4" Minimum bending radius: .55"

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/4-x-6-eye-eye-twin-path-high-performance-roundsling-vertical-cap-3...

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 1, 2026.