HIGH PERFORMANCE SLINGS > TWIN-PATH ENDLESS ROUNDSLINGS

14" x 8' Endless Twin-Path® High Performance Roundsling | Vertical Cap: 400,000 lbs.

SKU: TUFXKS40000-8 Item weight: 19.62 lbs

LENGTH	CAPACITY
8'	565,600 lbs.

SPECIFICATIONS

SKU	TUFXKS40000-8
Safety Factor	5.1
45 Degree Capacity	565,600 lbs.
60 Degree Capacity	692,800 lbs.
Vertical Capacity	400,000 lbs.
Choker Capacity	320,000 lbs.
Basket Capacity	800,000 lbs.
Length	8'
Minimum Connection Diameter	9.5"
Product Weight	19.62 lbs.
Additional Info	Nominal Body Width: 14" Minimum bending radius: 4.75" Tapered Body Width: 7"

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/14-x-8-endless-twin-path-high-performance-roundsling-vertical-cap-...

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 14, 2026.