LIFTING BEAMS AND SPREADER BARS > M&W UNIVERSAL LIFTING BEAM

M&W 12' Universal Lifting Beam & Spreader Beam - 20,000 lbs. WLL

SKU: ULB20K12-MW Item weight: 1,120 lbs

WORKING LOAD LIMIT	LENGTH	MATERIAL
20,000 lbs.	12'	Alloy Steel

SPECIFICATIONS

SKU	ULB20K12-MW
Working Load Limit (lbs.)	20,000 lbs.
Safety Factor	3:1
Rated for Overhead Lifting	Yes
Length	12'
Spread	12'
Shackle Size	Shackle #1 - 1-1/4" Shackle #2 - 7/8" Shackle #3 - 1-1/4"
Material	Alloy Steel
Finish	Painted
Color	Yellow
Product Weight	1120 lbs.
Standards	Exceeds all ASME B30.20 and OSHA regulations. Proof loaded per OSHA requirements.
Manufacturer Name	M&W
Brand Part Number	24665
Additional Info	Shackles not included Minimum sling length - 82"

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 16, 2026.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/m-w-12-universal-lifting-beam-20-000-lbs-wll

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 16, 2026.