LOAD CELLS > COMPRESSION LOAD CELLS

# Straightpoint® 25 T LoadSafe Compression Load Cell - WNI25TC

SKU: WNI-25-TC Item weight: 13.64 lbs

CAPACITY

**55,000 lbs.**

## SPECIFICATIONS

| | |
|---|---|
| **SKU** | WNI-25-TC |
| **Safety Factor** | 3:1 |
| **Load Capacity** | 55,000 lbs. |
| **Output** | Handheld |
| **Power Source** | 4 x AA Alkaline Batteries |
| **Accuracy** | +/- 0.1% of Full Scale |
| **Resolution** | 10 lbs. |
| **Range** | 3,280' |
| **Data Rate** | 3Hz - Configurable to 200Hz |
| **Operating Temperature** | -10° to +50°C \| 14° to 122° F |
| **Battery Life** | 1,200 hours continuous |
| **Product Weight** | 13.64 lbs. |
| **Standards** | IP67 |
| **Manufacturer Name** | Crosby Straightpoint |
| **Brand Part Number** | WNI25TC / 2789193 |


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.

## SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

**Current price & availability: heavyhaulrigging.com/p/straightpoint-25-t-loadsafe-compression-load-cell-wni25tc**


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.